



Iridium OpenPort

The Iridium OpenPort is designed for the maritime market and offers global voice and data service. Easy to install and set up, the Iridium OpenPort delivers up to three phone lines for simultaneous use and features always-on data with speeds up to 128 kbps on all IP backbone. The low-profile omni-directional antenna does not require a stabilization platform.

Flexible and attractive pricing packages provide a simplified pricing structure, voice being charged per minute and data per Megabyte.

Main features :

- Three separate phone lines
- High-speed data
- Flexible and attractive pricing packages
- Lightweight, low-profile satellite antenna
- Global coverage



Iridium OpenPort

Specifications

Antenna:

- Height: 9.06 in (230 mm)
- Diameter: 22.44 in (570 mm)
- Weight: 24.25 lb (11 kg)

Phone:

- 3 independent RJ11 ports for simultaneous use

Data:

- IP-based, 9.6-128 kbps (configurable) with per-MB pricing for airtime

Coverage:

- Global, pole-to-pole

Below Decks Unit:

- Height: 7.78 in (200 mm)
- Width: 9.84 in (250 mm)
- Diameter: 2.17 in (55 mm)
- Weight: 2.98 lb (1.35 kg)



The Iridium OpenPort standard package contains:

- Iridium OpenPort antenna/Above Deck Equipment (ADE)
- Iridium OpenPort antenna cable (20 meters)
- ADE Pole Bracket Mount
- Iridium OpenPort Below Deck Equipment (BDE)
- BDE power supply
- Cord, power supply
- BDE mounting bracket
- BDE mounting supply
- Captains desk phone
- Crew Calling desk phone
- Installation Manual (English) – ADE/BDE
- User Manual (English) – ADE/BDE

E-SAT

121 rue Aristide Briand – 92300 Levallois Perret – France

Tél. : +33 1 41 06 99 20 – Fax : +33 1 47 37 24 13

www.e-sat.fr – info@e-sat.fr