


COBHAM


SAILOR 4300 L-Band System


Installation guide















System Configuration - Example TT-4352A For further information, download the installation manual Above Deck Unit at www.cobham.com/satcom, Cobham SYNC Partner Portal, or from the distributor. Wired IP Handset PoE adapter TT-4338A Below Deck Unit 12-24 VDC 블 Recommended cable WLAN Notebook SIP Phone Wireless SIP Phones * Connector type: TNC Cable requirements: - Installation on bigger vessels: RG214/U up to 100 m length - Installation in a mechanically protected environment and shorter distances: RG223/U up to 25 m length



Any responsibility or liability for loss or damage in connection with the use of this product and the accompanying documentation is disclaimed by Thrane & Thrane A/S. The information purposes only, is subject to change without notice and may contain errors or inaccuracies. Manuals issued by Thrane & Thrane A/S are periodically revised and updated. Anyone relying on this information should acquire the most current version e.g. from www.cobham.com/satcom, Cobham SYNC Partner Portal, or from the distributor. Thrane & Thrane A/S is not responsible for the content or accuracy of any translations or reproductions, in whole or in part, of this manual from any other source. In the event of any discrepancies, the English version shall be the governing text. Thrane & Thrane A/S is trading as Cobham SATCOM.

Copyright © 2018 Thrane & Thrane A/S. All rights reserved.